



# “TWIS-TO-FLOOR®” 4000 SERIES CLEANOUTS



Flooring

Concrete

Figure No. 4020  
Finished Floor Cleanouts with  
“Twis-to-Floor” Adjustable Tops



Figure No. 4051

Figure No. 4020-FC with  
Clamping Device

## Versatility in Adjustment Before and After the Pour

### Benefits:

- Unique top assembly allows for interchangeability of scoriated, tile or terrazzo covers
- One size top assembly for 2-4” outlet ferrules
- Top frame stays in place when cover is removed

### Features:

- Thicker finished floor cover reinforced with support ribs for strength and durability
- Smooth outside surface of the top assembly and thread protector Styrofoam ring maximize adjustment during and after the finished floor concrete pour

# "TWIS-TO-FLOOR®" 4000 SERIES CLEANOUTS



Unfinished Floor Cleanout with Adjustable Round Cast Iron Tractor Cover Top  
Figure No. 4237



Unfinished Floor Cleanout with Adjustable Round Cast Iron Tractor Cover Top (Shown with Flashing Clamp)  
Figure No. 4240(-FC)



Finished Floor Cleanout with Adjustable Round Nickel Bronze Top - Figure No. 4031



Finished Floor Cleanout with Adjustable Round Nickel Bronze Top (Shown with Flashing Clamp)  
Figure No. 4020(-FC)



Unfinished Floor Cleanout with Adjustable Round Extra Heavy Duty Cast Iron Top (Shown with Flashing Clamp)  
Figure No. 4220(-FC)



Unfinished Floor Cleanout with Adjustable Round Extra Heavy Duty Cast Iron Top - Figure No. 4231



Finished Floor Cleanout with Adjustable Square Nickel Bronze Top (Shown with Flashing Clamp)  
Figure No. 4040(-FC)



Finished Floor Cleanout with Adjustable Square Nickel Bronze Top  
Figure No. 4051



## Exclusive Features:

- 2-4" ferrules provided with external machined thread for positive non-tilt engagement of adjustable top
- Machined ferrule provides positive non-tilt engagement for optional threaded anchor flange and clamping collar
- All 2, 3 & 4" ferrules regularly furnished with the same size slotted head plug as standard



## Ferrule Assembly Features:

- Top assembly offers easy attachment to ferrule.
- Easy to install clamping device.
- Cast iron clamping device providing maximum clamping force to the membrane.



**JAY R. SMITH MFG. CO.®**  
MEMBER OF MORRIS GROUP INTERNATIONAL

P.O. Box 3237 • Montgomery, AL 36109  
TEL: 334.277.8520 www.jrsmith.com

MEMBER OF

