S1605

⋖

NONE

4-14-06

SUPERSEDED

USE OF

WE CAN ASSUME NO RESPONSIBILITY FOR

WITHOUT NOTICE

AND CHANGE

TO MANUFACTURERS

DIMENSIONS ARE

IUMBER

NOTES:

2. Dimensions shown in

뚱

MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.j



LOCATION

SIPHONIC GUTTER DRAIN

6"(150) DIAMETER - LOW PROFILE GUTTER DRAIN

FUNCTION: For use in engineered siphonic roof drainage systems for gutters, parapets, small balconies, sills, cornices, marquees and other small overhanging areas where drainage of rainwater is required. Air baffle creates siphonic drainage action producing more efficient drainage than traditional gutter drains.




Fig. 1605T MALE THREADED OUTLET

REGULARLY FURNISHED:

Duco Cast Iron Body with Combination Flashing Clamp and Air Baffle.

U.S. Patent No. D576,257S

VARIATIONS:

Fig. 1605Y NO HUB OUTLET

Vandal Proof -U

OPTIONAL MATERIALS:

Galvanized Cast Iron -G

*As tested and certified by ANSI/ASME A112.6.9 "Siphonic Roof Drains" procedures and test apparatus.

IAPMO Listed File No. 5138

C B A	10-10-08 5-21-07 5-10-06	Added Patent No. Added Notes Added Notes	RN RN TBW	CL CL	VOLUME CUBIC FEET	FIGURE NUMBER 1605
REV.	DATE	DESCRIPTION	BY	CKD. BY		