DRAWING NUMBER

SUPERSEDED OR VOID DATA

WE CAN ASSUME NO RESPONSIBILITY FOR USE OF

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE

NONE

6-25-19

APPROVED BY:

CHECKED BY:

DRAWN BY

SCALE



JAY R.
SMITH MFG. CO.

MEMBER OF MORRIS GROUP INTERNATIONAL
POST OFFICE BOX 3227

MONTGOMERY, ALABAMA 36109-0237 (USA)
TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com

LOCATION

DRYWALL ACCESS DOORS





REGULARLY FURNISHED:

Doors are ideally suited for new installations or for remodeling, in masonry, tile, wood or other wall and ceiling surfaces. Door features rounded safety corners. Door and frame are fabricated from 16 gage, galvannealed steel with a prime coat finish. Frame is one piece construction, 1" wide and provides perfect concealment of the rough wall opening. Wall frame is provided with 1/4" mounting holes for fastening within the furred spaces allowing faster installation and fixing maximum clearance. Concealed pivoting rod hinge prevents distortion and closes door squarely. Doors 24" or larger are provided with a continuous piano hinge. Latch is screwdriver operated. Finish is a prime coat suitable for painting.

GUIDE SPECIFICATIONS:

Provide 470 Series, Drywall Access Doors (specify options). Access door and frame shall be fabricated from 16 gage, galvannealed steel with a prime coat finish. The door shall have rounded safety corners and a concealed pivoting rod hinge. Frame shall be one piece construction with no miters or welds on the face. Latch shall be screwdriver operated. Finish shall be a prime coat suitable for painting.





- (1) Concealed pivoting rod hinge
- 2 Door
- ③ Frame
- 4 Screwdriver operated latch
- (5) Mounting holes

VARIATIONS:

Allen Key Latch -AK Cylinder Lock (one per door) -CL Stainless Steel Construction (See Fig. 472)

| DCBA | 02-19-20 02-12-20 02-10-20 01-31-20 | Added Allen Key Latch to Var. Revised Header Rem. Allen Key Latch from Var. Revised Variations | MW MW MW MW | CL JM JM JM | - | CUBIC FEET | FIGURE NUMBER 470 SERIES |
|------|--|---|----------------------|----------------------|---|------------|---------------------------------------|
| REV. | DATE | DESCRIPTION | BY | CKD. BY | | | · · · · · · · · · · · · · · · · · · · |

DRAWING NUMBER S470 BS

⋖

NONE

PA

ΒΥ:

APPROVED

CHECKED BY

DRAWN BY

FIGURE NUMBER

亨

ξ

SUPERSEDED OR VOID DATA

Р

CAN ASSUME NO RESPONSIBILITY FOR USE

WE

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE



JAY R.
SMITH MFG. CO.

MEMBER OF MORRIS GROUP INTERNATIONAL
POST OFFICE BOX 3237
MONTGOMERY, ALABAMA 36109-0237 (USA)
TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com

DRYWALL ACCESS DOORS

NOMINAL **DOOR SIZE CEILING OPENING LATCHES WEIGHT** (W X H) (minimum required) 470 6" x 6" 6-1/2" x 6-1/2" 3 lbs. 470 8" x 8" 8-1/2" x 8-1/2" 3 lbs 470 8" x 12" 8-1/2" x 12-1/2" 4 lbs. 10" x 10" 10-1/2" x 10-1/2" 470 1 4 lbs. 12" x 12" 12-1/2" x 12-1/2" 470 1 5.5 lbs. 12" x 16" 470 12-1/2" x 16-1/2' 6 lbs. 470 12" x 18' 12-1/2" x 18-1/2' 2 6.5 lbs 12-1/2" x 24-1/2" 14-1/2" x 14-1/2" 14-1/2" x 20-1/2" 470 12" x 24' 3 9.5 lbs 470 14" x 14' 6 lbs. 14" x 20" 470 3 8 lbs. 470 14" x 24" 14-1/2" x 24-1/2" 3 15 lbs 15" x 15" 15-1/2" x 15-1/2" 470 6.5 lbs 16" x 16" 470 16-1/2" x 16-1/2" 7.5 lbs 470 16" x 20" 16-1/2" x 20-1/2" 3 8.5 lbs 470 16" x 24" 16-1/2" x 24-1/2" 3 10 lbs. 470 1<u>8" x 18"</u> 18-1/2" x 18-1/2" 3 9 lbs. 18" x 24" 18-1/2" x 24-1/2' 470 5 12 lbs. 18" x 36' 470 18-1/2" x 36-1/2" 6 16 lbs. 470 20" x 20" 20-1/2" x 20-1/2" 3 11 lbs. 20-1/2" x 24-1/2" 20-1/2" x 30-1/2" 470 20" x 24" 5 13 lbs. 20" x 30" 470 5 15 lbs. 22" x <u>22</u>" 22-1/2" x 22-1/2" 470 3 12 lbs. 22" x 30" 22-1/2" x 30-1/2" 470 5 16 lbs. 24" x 24" 24-1/2" x 24-1/2" 470 3 15 lbs. 470 24" x 30" 24-1/2" x 30-1/2" 17 lbs. 5 470 24" x 36" 24-1/2" x 36-1/2" 6 20.5 lbs 24" x 48" 24-1/2" x 48-1/2" 470 7 28 lbs. 470 30" x 30" 30-1/2" x 30-1/2' 7 21.5 lbs 32" x 32" 470 32-1/2" x 32-1/2" 7 23 lbs. 470 36" x 36" 8 31.5 lbs. 36-1/2" x 36-1/2" 36-1/2" x 48-1/2" 48-1/2" x 48-1/2" 470 36" x 48" 9 45 lbs. 48" x 48" 470 11 58 lbs

| B A | 08-24-20 02-13-20 | Revised Latches Revised Header | MW MW | | - | VOLUME CUBIC FEET | FIGURE NUMBER 470 BS |
|--------|----------------------|-----------------------------------|----------|---------|---|----------------------|----------------------|
| REV. | DATE | DESCRIPTION | BY | CKD. BY | | | |