

JAY R. **SMITH** MFG. CO.[®] MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396



LOCATION

S4767

DRAWING NUMBER ⋖

NONE

CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA 3-9-15

APPROVED

WITHOUT NOTICE

TO MANUFACTURERS TOLERANCE AND CHANGE

M


₽ ٥

TBW DRAWN BY

PLASTERED WALL ACCESS DOOR



- (1) Concealed pivoting rod hinge
- ② Frame
- 3 Mounting holes
- 4 Ceramic tile over plaster
- ⑤ Screwdriver operated latch
- 6 Door
- 7 Finish line, plaster over




SIDE VIEW

REGULARLY FURNISHED:

Doors are designed specifically to meet the needs of plaster construction. Door has 3/4" plaster ground for plaster finish. Door and frame are fabricated from 14 gauge, type 304, stainless steel with a satin finish on exposed surface. Frame has 1/4" mounting holes to facilitat installation. Concealed pivoting rod hinge prevents distortion and closes door squarely. Latch is screwdriver operated.

GUIDE SPECIFICATION:

Provide 4767 Series, Plastered Wall Access Doors (specify options). Access door and frame shall be fabricated from 14 gauge, type 304, stainless steel with a satin finish on exposed surface. The door shall have a concealed pivoting rod hinge and a screwdriver operated latch.



FRONT VIEW

	ilable upon request		
NOMINAL DOOR SIZE	CEILING OPENING		
(W X H)	(minimum required)	I ATCHES	WEIG
4767 8" x 8"	8-1/4" x 8-1/4"	1	3.5
		1	
	8-1/4" x 12-1/4"	•	5
4767 10" x 10"	10-1/4" x 10-1/4"	1	5.5
4767 12" x 12"	12-1/4" x 12-1/4"	1	6
4767 12" x 16"	12-1/4" x 16-1/4"	1	7.5
4767 12" x 18"	12-1/4" x 18-1/4"	1	8.5
4767 12" x 24"	12-1/4" x 24-1/4"	3	12
4767 14" x 14"	14-1/4" x 14-1/4"	2	7.5
4767 16" x 16"	16-1/4" x 16 1/4"	2	9.5
4767 16" x 20"	16-1/4" x 20-1/4"	2	12
4767 18" x 18"	18-1/4" x 18-1/4"	2	11
4767 18" x 24"	18-1/4" x 24-1/4"	3	17.5
4767 20" x 24"	20-1/4" x 24-1/4"	3	21
4767 20" x 30"	20-1/4" x 30-1/4"	3	22
4767 24" x 24"	24-1/4" x 24-1/4"	3	20
4767 24" x 30"	24-1/4" x 30-1/4"	3	23.5
4767 24" x 36"	24-1/4" x 36-1/4"	3	27
4767 30" x 30"	30-1/4" x 30-1/4"	3	30
4767 36" x 36"	36-1/4" x 36-1/4"	3	38

VARIATIONS:

- Allen Key Latch -AKL
- Cylinder Lock (one per door) -CL
 - 16 Guage, Galvannealed Steel, Prime
 - Coated Construction. (See Fig. 4765)

					_	VOLUME CUBIC FEET	FIGURE NUMBER
Α	7-25-18	Revised Reg. Furn., Guide Specs.	TBW	CL			4767
REV.	DATE	DESCRIPTION	BY	CKD. BY			7/0/