

construction and provide the security required in today's schools, hospitals, hotels, and correctional institutions. Door and frame are fabricated from 14 gage, galvannealed steel and the door is provided with a 16 gage vertical reinforcement channel. Lock is an automatic spring bolt type featuring a precision mechanism. When the door is closed in the locked position, the uniquely designed angled cam lock automatically engages. The key can only be removed when the lock is in the locked position. Hinge is a concealed type. Doors 24" or larger are supplied with a continuous piano hinge. Finish is a prime coat suitable

GUIDE SPECIFICATION:

for painting.

ш

DRAWING NUMBER S4782

SIZE ٩

SCALE:

DATE:

В. SJM APPROVED

CHECKED BY ۲

TBW DRAWN BY:


4782

NONE

3-18-15

Provide 4782 Series, Shur-Lok Access Doors. Access door and frame shall be fabricated from 14 gage, galvannealed steel with a prime coat finish. Door shall have a 16 gage vertical reinforcement channel, a concealed hinge, and an automatic locking, spring bolt lock. Finish shall be a prime coat suitable for painting.

	STANDARD AVAILABLE SIZES Special sizes available upon request								
DOC	MINAL OR SIZE V X H)		WEIGHT						
4782	<u>v л п)</u> 8" х 8"	(Minimum Required) 8-1/2" x 8-1/2"	4 lbs.						
	10" x 10"	10-1/2" x 10-1/2"	5.5 lbs.						
4782	12" x 12"	12-1/2" x 12-1/2"	7 lbs.						
4782	14" x 14"	14-1/2" x 14-1/2"	8 lbs.						
4782	16" x 16"	16-1/2" x 16-1/2"	10 lbs.						
4782	18" x 18"	18-1/2" x 18-1/2"	12 lbs.						
4782	18" x 24"	18-1/2" x 24-1/2"	16 lbs.						
4782	22" x 22"	22-1/2" x 22-1/2"	17.5 lbs.						
4782	24" x 24"	24-1/2" x 24-1/2"	20.5 lbs.						
4782	24" x 30"	24-1/2" x 30-1/2"	24 lbs.						
4782	24" x 36"	24-1/2" x 36-1/2"	28 lbs.						
4782	36" x 36"	36-1/2" x 36-1/2"	41.5 lbs.						



	Ι.							
						-		FIGURE NUMBER
FIGURE NUMBER	B A	A C 40 4F	Rev. Reg. Furn., Rev. Variations Revised Table	MW TBW	JM SJM	POUNDS	CUBIC FEET	4782
	REV.	DATE	DESCRIPTION	BY	CKD. BY			

