

GUIDE SPECIFICATION:

Provide 4783 Series, Valve Box (specify options). Access door and frame shall be fabricated from 16 gage, galvannealed steel with a prime coat finish. The door shall have rounded safety corners and a concealed continuous piano hinge. Frame shall be one piece construction with no miters or welds on the face. Latch shall be screwdriver operated. Valve box shall be fully enclosed with 16 gage, galvannealed steel with a prime coat finish. Finish shall be a prime coat suitable for painting.

Frame is a one piece construction 1" wide and

mounting holes for fastening within the furred spaces allowing faster installation and giving maximum clearance. Hinge is a concealed continuous piano hinge. Latch is screwdriver operated. Finish is a prime coat suitable for painting.

produces perfect concealment of the rough wall openings. Wall frame is provided with 1/4"

	STANDARD AVAILABLE SIZES Special sizes available upon request						
NOMINAL DOOR SIZE (W X H X Depth)	WALL OPENING	LATCH	WEIGHT				
4783 8" x 8" x 4"	8-1/2" x 8-1/2"	1	10.0 lbs.				
4783 12" x 12" x 4"	12-1/2" x 12-1/2"	1	18.0 lbs.				
4783 12" x 12" x 6"	12-1/2" x 12-1/2"	1	20.0 lbs.				
4783 14" x 14" x 4"	14-1/2" x 14-1/2"	1	26.0 lbs.				
4783 14" x 14" x 6"	14-1/2" x 14-1/2"	1	28.0 lbs.				
4783 16" x 16" x 4"	16-1/2" x 16-1/2"	1	32.0 lbs.				
4783 16" x 16" x 6"	16-1/2" x 16-1/2"	1	34.0 lbs.				

VARIATIONS:
Allen Key Latch -AKL
Cylinder Lock -CL
Stainless Steel Construction -SS
Type 304 No. 4 Satin Finish
T Handle -TH

					WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER
Α	6-18-15	Revised Table	TBW	SJM			4783
REV.	DATE	DESCRIPTION	BY	CKD. BY			4703