

GENERAL PURPOSE FLOOR DRAIN WITH ADJUSTABLE STRAINER HEAD

DRAWING NUMBER **S9600**

SIZE **A**

SCALE: **NONE**

DATE: **7-16-14**

APPROVED BY: **JM**

CHECKED BY: **CL**

DRAWN BY: **TBW**

FIGURE NUMBER **9600**

WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE

"A" Strainer

<input type="checkbox"/>	A05SS
<input type="checkbox"/>	A06SS

"B" Strainer

<input type="checkbox"/>	B05SS
<input type="checkbox"/>	B06SS

MIN	MAX
1/2(13)	1 1/2(38)

MIN	MAX
7/8(22)	1 1/2(38)

A (Pipe Size) = 02(50), 03(75), or 04(100)

USDA ACCEPTED

ASME A112.6.3 & CSA B79
Certified Light Duty Load

File No. 3663

<input type="checkbox"/> Fig. 9600BW	BUTTWELD OUTLET ▲
<input type="checkbox"/> Fig. 9600T	THREADED OUTLET
<input type="checkbox"/> Fig. 9600Y	NO-HUB OUTLET

▲ Schedule 40 Regularly Furnished

REGULARLY FURNISHED:

14 Gauge Type 304 Stainless Steel Body with Flashing Collar and Adjustable Cast Strainer Head (As Indicated) with No. 4 Finish.

VARIATIONS:

- Sediment Bucket -B
- Vandal Proof Screws -U
- Less Seepage Holes -LSH
- 1/2"(13) Trap Primer Connection -P050
- USDA Compliant

OPTIONAL MATERIALS:

- Type 316 Stainless Steel -316

SUBJECT TO MANUFACTURING TOLERANCE AND CHANGE WITHOUT NOTICE.

NOTE: Dimensions shown in parentheses are in millimeters.

REV.	DATE	DESCRIPTION	BY	CKD. BY	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER
		Added ASME & CSA numbers Revised Certified Duty Capacity Revised Certified Duty Capacity Revised Variations, Added Note	KK KK KK TBW	CL CL CL CL			9600