DRAWING NUMBER

CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA

Ŋ

TOLERANCE AND CHANGE WITHOUT NOTICE


SUBJECT TO MANUFACTURERS .

FLOOR DRAINS STAINLESS STEEL - CARBON STEEL

8 1/2" (215) ROUND MEDIUM DUTY TOP WITH EXTENDED INTEGRAL FLANGE FOR WELDING TO STEEL DECKS

FUNCTION: Used in areas where drain body is welded to deck or where waterproof traffic floor coverings are applied, and where a corrosion resistant drain is required.

> Free Area 20.50 SQ IN (132) SQ CM



A (Pipe Size) = 02(50), 03(75) or 04(100)

Schedule 40 Regularly Furnished

Butt Weld Outlet

Fig. 9705C CAULK OUTLET Fig. 9705T THREADED OUTLET

REGULARLY FURNISHED:

CF8 (Equivalent to Type 304) Rough Finish Stainless Steel Body and Loose Set Non-Tilt Grate.

Design Pressures and Temperatures

- 1. With proper outlet connection, shall be watertight up to 10 ft. of water column (4.34 psig).
- 2. When exposed to effluent appropriate for drain material, the drain shall withstand effluent temperatures of 180 degrees F at ambient pressure.

VARIATIONS:

4(100) or 6"(150) Dia. Funnel (Specify Fig. 9703)

8 3/4(220) x 3 3/4"(95) Funnel (Specify Fig. 9704)

Satin Finished Top -SF Sediment Bucket -B

Solid Scoriated Cover -SC Vandal Proof Grate -U

For 90° Outlet (Specify Fig. 9759) BW Butt Weld Outlet (Specify Schedule -S05, -S10 or -S40)

NOTE: Dimensions shown in

parentheses are in millimeters.

OPTIONAL MATERIALS:

CF8M (Equivalent to Type 316)

A-27 Carbon Steel -A27

Cast Iron Grate -CIG

Stainless Steel -316

Nickel Bronze Grate -NB

Polished Bronze Grate -PB

E D CB		Added Note Revised Variations Changed Metric Equivalents Added Millimeters	TBW RN JJ EMB	CL CL BS BS	 VOLUME CUBIC FEET	FIGURE NUMBER 9705
REV.	DATE	DESCRIPTION	BY	CKD. BY		