<u>P/N</u>	Engineering Specifications
MPAV21TKO3A2IP	MPAV/Pall 21TKO series housing 10" dia x 44" high, 304 stainless steel construction with 2" male NPT ports and V- clamp cover closure. 150 psi pressure rating. Contains 7 Pall CLR10-30 filter elements rated 10 microns. Clean pressure drop = 2.0 psid at 75 gpm. Includes 1 year supply filter elements + element change-out labor. Source: Woods & Jaye Sales - Phone 718-786-8260
MPAV48FMO4316L3FIP	MPAV/Pall 48FMO series housing 12" dia x 66" high, 316 stainless steel construction with 3" ANSI RF flange ports and swing bolt cover closure. 150 psi pressure rating. Contains 12 Pall CLR 10-40 filter elements rated 10 microns. Clean pressure drop = 2.7 psid at 200 gpm. Includes 1 year supply filter elements + element change- out labor. Source: Woods & Jaye Sales – Phone 718-786-8260
MPAV84FMO4316L4FIP	MPAV/Pall 84FMO series housing 16" dia x 67" high, 316 stainless steel construction with 4" ANSI RF flange ports and swing bolt cover closure. 150 psid pressure rating. Contains 21 Pall CLR 10-40 filter elements rated 10 microns. Clean pressure drop = 4.0 psid at 400 gpm. Includes 1 year supply filter elements + element change-out labor. Source: Woods & Jaye Sales – Phone 718-786-8260